

Product Data Sheet

Aspire Bullnose Paver – Elongated with Legs

Description:

The Aspire Elongated Bullnose Paver with Legs securely fits into the grid like the rest of the pavers. It is extended so it matches up with the paver in the field eliminating the need to cut an inch off the end of the grid.

Benefits:

- Compatible with Aspire Resurfacing Pavers
- Provides an attractive rounded edge
- Hides the side of the Aspire Grid
- Legs fit into the grid and when used with adhesive it creates a more secure border



Bottom view

Physical Properties

Property	Value	
Dimensions	4" width x 9" length x 0.75" thick (Grid Coverage 4"x8")	
Weight	16 oz	
Height with Grid	1.75"	
Colors	Available in all Classic and Designer colors	

Specification	Test Method	Result
Fire Classification	ASTM E108-007	Class A
2" Hail Impact	UL-2218	Class 4
Compression Strength	ASTM C140-09 Section 7	3521 PSI
Flexural Modulus	ASTM C140-09	3842 PSI
Water Absorption	ASTM C67 Section 8	4.10%
Freeze-Thaw	ASTM C67 Section 9	Pass: No sign of cracking or disintegration
Freeze-Thaw Cycling	ASTM C67	Pass
Specific Gravity	FSBP Test Method	0.9
Coefficient of Friction with Pull Monitor	ASTM C1028-07	Wet: 0.47 Dry: 0.83
Chemical Resistance	ASTM F925	No dulling, color change, or surface attack

Aspire by Brava 915 E. Tyler Street | Washington, IA 52353 | ©2023 Brava Roof Tile For more information please visit aspirepavers.com or call 844-290-4196 09/23

